

TOPIA






Optimise your urban space lighting with minimised energy costs



Experience the exceptional efficiency of TOPIA, the ultimate urban lighting solution that provides superior photometric performance in a typically timeless urban design. Seamlessly integrating state-of-the-art lighting technologies, TOPIA perfectly balances efficiency, performance and functionality. This urban luminaire guarantees an outstanding lighting experience with the fastest return on investment.

Its universal fixation system allows for easy switching between post-top and side-entry positions, eliminating the need for disconnection or additional effort, ensuring maximum flexibility and adaptability for any lighting application. A dedicated post-top arm is also available to ensure an elegant and consistent integration into all types of urban spaces. Encounter a new urban lighting approach with TOPIA, the highly efficient, durable and functional luminaire.



URBAN &
RESIDENTIAL
STREETS



BRIDGES



BIKE &
PEDESTRIAN
PATHS



RAILWAY
STATIONS &
METROS



CAR PARKS



SQUARES &
PEDESTRIAN
AREAS

Concept

TOPIA is a combination of the latest lighting technologies in a functional urban design, resulting in a powerful yet user-friendly lighting solution.

The luminaire is made of recyclable materials, such as aluminium and glass, and is designed to promote the principles of a circular economy through its accessible and replaceable components. This makes it easy to maintain and prolongs the lifecycle of the product. Its pure and typically timeless urban design allows TOPIA to suit any city landscape.

Whether for residential areas, urban streets, public squares, bike paths, bridges, or parking lots, TOPIA can be tailored to meet any specific lighting needs. It relies on advanced photometric technologies to precisely meet the unique demands of lighting projects and comply with local regulations. The LensoFlex®4 and HiFlex™ platforms offer flexible, energy-efficient photometric solutions that can be tailored to meet the requirements of any lighting project while maximising savings and providing a quick return on investment.

As your partner for urban nightlife, TOPIA is an environmentally-friendly luminaire compatible with the preservation of nighttime flora and fauna.

TOPIA features a universal fixation system, which allows for easy post-top and side-entry installation on a variety of spigot sizes (Ø48-Ø60mm). This system enables TOPIA to be easily repositioned without the need to remove it from the pole, offering unparalleled flexibility in pole and bracket configurations. TOPIA can also be mounted on a post-top arm designed for Ø48-Ø60mm spigots. For added convenience during installation and maintenance, the luminaire offers optional tool-free access to the gear compartment.

TOPIA is a connected-ready luminaire that can be equipped with optional NEMA or Zhaga sockets, enabling it to easily integrate with various connected lighting systems.



TOPIA is an energy-efficient lighting solution that provides optimised total cost of ownership in a timeless urban design.



DarkSky
Approved

TOPIA provides eco-friendly lighting compatible with the preservation of nighttime flora and fauna.



This urban luminaire offers a connected-ready lighting solution compatible with a NEMA or a Zhaga socket.



Its universal fixation system allows for easy switching between post-top and side-entry positions, simplifying the ordering and installation process.


TYPES OF APPLICATION

- URBAN & RESIDENTIAL STREETS
- BRIDGES
- BIKE & PEDESTRIAN PATHS
- RAILWAY STATIONS & METROS
- CAR PARKS
- SQUARES & PEDESTRIAN AREAS


KEY ADVANTAGES

- Cost-effective and efficient lighting solution for a fast return on investment
- HiFlex photometric engine designed for optimised energy efficiency
- LensoFlex®4 versatile solutions for high-end photometrics maximising comfort and safety
- Connected-ready
- Post-top mounting with a dedicated bracket
- On-site adjustment from post-top to side-entry without disconnecting the luminaire from the pole
- Zhaga-D4i certified

TOPIA | Universal slip-over mounting for Ø48-60mm spigots - 2xM8 screws



TOPIA | Dedicated bracket for post-top mounting on Ø48-Ø60mm spigots - 2XM8 screws





LensoFlex®4

LensoFlex®4 maximises the heritage of the LensoFlex® concept with a very compact yet powerful photometric engine based upon the addition principle of photometric distribution. The number of LEDs in combination with the driving current determines the intensity level of the light distribution. With optimised light distributions and very high efficiency, this fourth generation enables the products to be downsized to meet application requirements with an optimised solution in terms of investment.

LensoFlex®4 optics can feature backlight control to prevent intrusive lighting, or a glare limiter for high visual comfort.



HiFlex™

The HiFlex™ platform is expertly designed to optimise energy efficiency. Its photometric engines feature high-power LEDs that deliver exceptional performance while consuming minimal energy, resulting in unmatched efficacy (lm/W).


Ideal for projects that require a streamlined approach to maximising lighting efficacy and achieving swift ROI, HiFlex™ is available in two versions: HiFlex 1, boasting 24 LEDs and HiFlex 2, equipped with 36 LEDs. Both variants are designed with the priorities of compactness, cost-effectiveness and high performance in mind.



Custom dimming profile

Intelligent luminaire drivers can be programmed with complex dimming profiles. Up to five combinations of time intervals and light levels are possible. This feature does not require any extra wiring.

The period between switching on and switching off is used to activate the preset dimming profile. The customised dimming system generates maximum energy savings while respecting the required lighting levels and uniformity throughout the night.




A. Dimming level | B. Time




Daylight sensor / photocell

Photocell or daylight sensors switch the luminaire on as soon natural light falls to a certain level. It can be programmed to switch on during a storm, on a cloudy day (in critical areas) or only at nightfall so as to provide safety and comfort in public spaces.



The Zhaga consortium joined forces with the DiiA and produced a single Zhaga-D4i certification that combines the Zhaga Book 18 version 2 outdoor connectivity specifications with the DiiA's D4i specifications for intra-luminaire DALI.



Standardisation for interoperable ecosystems



As a founding member of the Zhaga consortium, Schréder has participated in the creation of, and therefore supports, the Zhaga-D4i certification program and the initiative of this group to standardise an interoperable ecosystem. The D4i specifications take the best of the standard DALI2 protocol and adapt it to an intra-luminaire environment but it has certain limitations. Only luminaire mounted control devices can be combined with a Zhaga-D4i luminaire.

According to the specification, control devices are limited respectively to 2W and 1W average power consumption.

Certification program

The Zhaga-D4i certification covers all the critical features including mechanical fit, digital communication, data reporting and power requirements within a single luminaire, ensuring plug-and-play interoperability of luminaires (drivers) and peripherals such as connectivity nodes.

Cost-effective solution

A Zhaga-D4i certified luminaire includes drivers offering features that had previously been in the control node, like energy metering, which has in turn simplified the control device therefore reducing the price of the control system.

Schréder EXEDRA is the most advanced lighting management system on the market for controlling, monitoring and analysing streetlights in a user-friendly way.



Standardisation for interoperable ecosystems

Schréder plays a key role in driving standardisation with alliances and partners such as uCIFI, TALQ or Zhaga. Our joint commitment is to provide solutions designed for vertical and horizontal IoT integration. From the body (hardware) to the language (data model) and the intelligence (algorithms), the complete Schréder EXEDRA system relies on shared and open technologies. Schréder EXEDRA also relies on Microsoft Azure for cloud services, provided with the highest levels of trust, transparency, standards conformance and regulatory compliance.

Breaking the silos


With EXEDRA, Schréder has taken a technology-agnostic approach: we rely on open standards and protocols to design an architecture able to interact seamlessly with third-party software and hardware solutions. Schréder EXEDRA is designed to unlock complete interoperability, as it offers the ability to:

- control devices (luminaires) from other brands
- manage controllers and to integrate sensors from other brands
- connect with third-party devices and platforms

A plug-and-play solution

As a gateway-less system using the cellular network, an intelligent automated commissioning process recognises, verifies and retrieves luminaire data into the user interface. The self-healing mesh between luminaire controllers enables real-time adaptive lighting to be configured directly via the user interface. OWLET IV luminaire controllers, optimised for Schréder EXEDRA, operate Schréder's luminaires and luminaires from third parties. They use both cellular and mesh radio networks, optimising geographical coverage and redundancy for continuous operation.

Tailored experience



Schréder EXEDRA includes all advanced features needed for smart device management, real-time and scheduled control, dynamic and automated lighting scenarios, maintenance and field operation planning, energy consumption management and third-party connected hardware integration. It is fully configurable and includes tools for user management and multi-tenant policy that enables contractors, utilities or big cities to segregate projects.

A powerful tool for efficiency, rationalisation and decision making


Data is gold. Schréder EXEDRA brings it with all the clarity managers need to drive decisions. The platform collects massive amounts of data from end devices and, aggregates, analyses and intuitively displays them to help end-users take the right actions.

Protected on every side



Schréder EXEDRA provides state-of-the-art data security with encryption, hashing, tokenisation, and key management practices that protect data across the whole system and its associated services. The whole platform is ISO 27001 certified. It demonstrates that Schréder EXEDRA meets the requirements for establishing, implementing, maintaining and continually improving security management.

Mobile App: any time, any place, connect to your street lighting




The Schréder EXEDRA mobile application offers the essential functionalities of the desktop platform, to accompany all types of operator on site in their daily effort to maximise the potential of connected lighting. It enables real-time control and settings, and contributes to effective maintenance.

With the PureNight concept, Schréder offers the ultimate solution for restoring the night sky without switching off cities, while maintaining safety and well-being for people and preserving wildlife. The PureNight concept guarantees that your Schréder lighting solution satisfies environmental laws and requirements. Well-designed LED lighting has the potential to improve the environment in all respects.



Direct the light only where it is wanted and needed



1. Without backlight
2. With backlight

Schréder is renowned for its expertise in photometry. Our optics direct light only where it is wanted and needed. However, light trespass behind the luminaire might be a key concern when it comes to protecting a sensitive wildlife habitat or avoiding intrusive lighting towards buildings. Our fully integrated backlight solutions easily address this potential risk.

Protect wildlife



If not well designed, artificial lighting can badly affect wildlife. Blue light and excessive intensity can have a damaging effect on all types of life. Blue light radiation has the ability to suppress the production of melatonin, the hormone that contributes to the regulation of the circadian rhythm. It can also alter the behavioural patterns of animals including bats and moths, as it can change their movements towards or away from light sources. Schréder

favours warm white LEDs with minimal blue light, combined with advanced control systems including sensors. This enables permanent adaptation of the lighting to the real needs of the moment, minimising disturbance to the fauna and flora.

Choose a DarkSky Approved luminaire



DarkSky International is the recognised authority on light pollution. It provides leadership, tools and resources to industries and companies willing to reduce light pollution. The DarkSky Approved Luminaires Program certifies outdoor lighting fixtures as being Dark Sky Friendly. This luminaire is part of our approved range of luminaires that comply with the Approval Programme and provide light that is environmentally friendly in every way.

Offer maximum visual comfort to people



Because of the lower installation height compared to road lighting, visual comfort is an essential aspect of urban lighting. Schréder designs lenses and accessories to minimise any type of glare (distracting, discomforting, disabling glare and blinding glare). Our design offices harness a range of possibilities to find the best solutions for each project and ensure that we provide a gentle light that delivers the best night-time experience.


GENERAL INFORMATION		ELECTRICAL INFORMATION	
Recommended installation height	m to m ' to '	Electrical class	Class I EU, Class II EU
Circle Light label	Score ≥90 - The product fully meets circular economy requirements	Nominal voltage	120-277V – 50-60Hz 220-240V – 50-60Hz
Driver included	Yes	Surge protection options (kV)	10
CE mark	Yes	Control protocol(s)	1-10V, DALI
UKCA marking	Yes	Control options	AmpDim, Bi-power, Custom dimming profile, Photocell, Remote management
ENEC certified	Yes	Socket	Zhaga (optional) NEMA 7-pin (optional)
ENEC+ certified	Yes	Associated control system(s)	Schréder EXEDRA
Zhaga-D4i certified	Yes	OPTICAL INFORMATION	
DarkSky Approved	Yes	LED colour temperature	2200K (Warm White WW 722) 2700K (Warm White WW 727) 3000K (Warm White WW 730) 3000K (Warm White WW 830) 4000K (Neutral White NW 740)
· DarkSky Approved with 3000K or warmer CCT and tilt limiter option selected		Colour rendering index (CRI)	>70 (Warm White WW 722) >70 (Warm White WW 727) >70 (Warm White WW 730) >80 (Warm White WW 830) >70 (Neutral White NW 740)
HOUSING AND FINISH		ULOR	0%
Housing	Aluminium	ULR	0%
Optic	PMMA	· DarkSky Approved when fitted with LEDs of 3000K or less. · ULOR may be different according to the configuration. Please consult us. · ULR may be different according to the configuration. Please consult us.	
Protector	Tempered glass	LIFETIME OF THE LEDS @ TQ 25°C	
Housing finish	Polyester powder coating	All configurations	100,000h - L95
Standard colour(s)	AKZO grey 900 sanded	· Lifetime may be different according to the size/configurations. Please consult us.	
Tightness level	IP 66		
Impact resistance	IK 09		
Vibration test	Compliant with modified IEC 68-2-6 (0.5G)		
Access for maintenance	Tool-less access to gear compartment (option)		
· Any other RAL or AKZO colour upon request			
OPERATING CONDITIONS			
Operating temperature range (Ta)	-30°C up to +55°C / -22°F up to 131°F with wind effect		
· Depending on the luminaire configuration. For more details, please contact us.			

DIMENSIONS AND MOUNTING

AxBxC (mm inch)	450x105x450 17.7x4.1x17.7
Weight (kg lbs)	5.5-6.2 12.1-13.6
Aerodynamic resistance (CxS)	0.04
Mounting possibilities	On a dedicated post-top arm for Ø48-Ø60mm spigots Side-entry slip-over – Ø48mm Side-entry slip-over – Ø60mm Post-top slip-over – Ø48mm Post-top slip-over – Ø60mm

· DarkSky Approved when a tilt limiter option is selected

· Dimensions given with Ø60mm spigot (side-entry mounting)





Luminaire output flux (lm)								Power consumption (W)	Luminaire efficacy (lm/W)
Warm White WW 722		Warm White WW 727		Warm White WW 730		Neutral White NW 740			
Number of LEDs	Min	Max	Min	Max	Min	Max	Min	Max	Up to
24	1600	4900	1800	5500	1900	5700	2000	6200	144
36	2400	5600	2800	6300	2900	6500	3100	7000	143
48	3300	8700	3700	9800	3800	10200	4100	11000	151
72	3800	10000	4300	11300	4500	11700	4900	12600	149

Tolerance on LED flux is $\pm 7\%$ and on total luminaire power $\pm 5\%$



Luminaire output flux (lm)								Power consumption (W)	Luminaire efficacy (lm/W)				
Warm White WW 722		Warm White WW 727		Warm White WW 730		Warm White WW 830		Neutral White NW 740					
Number of LEDs	Min	Max	Min	Max	Min	Max	Min	Max	Up to				
10	600	1900	600	2100	700	2200	600	2100	700	2400	7	22	138
20	1200	4000	1300	4400	1400	4700	1300	4400	1500	5100	13	44	145
30	1800	5800	2000	6400	2100	6800	2000	6400	2300	7400	19	60	151
40	2400	7000	2700	7700	2800	8200	2700	7700	3100	8900	25	67	154

Tolerance on LED flux is $\pm 7\%$ and on total luminaire power $\pm 5\%$

